

# ISDN TELEPHONE

Delivering on  
the Promise of ISDN

# SRS<sup>®</sup> -9912-SP/9924

## Get the Most from Your Centrex Service

The Fujitsu SRS-9912-SP ISDN set is designed to help you enjoy all of the advanced features of your voice Centrex service, providing full Key System functionality without the hardware and wiring associated with Key Systems or PBXs. The SRS-9912-SP has 6 programmable keys for call appearances and network features, along with a two-way speakerphone for superior hands-free operation. The 2 line by 24 character display provides easy viewing of calling number information and network messages.



## Get Superior Centrex with the SRS-9924

The SRS-9924 ISDN set has 17 programmable keys for call appearances, network features or speed dialing, along with a two-way speakerphone and large personal directory. An optional SRS-9924 add-on-button module (ABM) provides 30 additional keys for support of demanding call coverage applications and increased speed dial capability. The SRS-9924 is the perfect solution for a broad range of applications in your office.



\*Sets available in black or white.

**FUJITSU**

# SRS-9912-SP/9924

Delivering on  
the Promise of ISDN

## Features and Specifications

### Voice Features

“Auto answer” call announce  
Call preferences  
Call appearance reservation  
Full Key System functionality  
One-button access to advanced Centrex features  
Speakerphone for hands-free operation  
One-touch speed dialing  
Programable Smartpause feature  
Simplified Conference, Transfer and Hold  
Fully automatic last number redial capability  
Headset/handset operation  
Hearing aid compatible handset  
Handset volume control (ADA compliant)  
Personal directory (32 items)  
Call duration display  
Unanswered call logging (up to 8 calls)  
Ringer volume options, including “extra high”  
Ringer mode options, including mute ring or one ring  
LCD display of 2 lines by 24 characters  
Message Waiting LED  
DTMF support for non-ISDN applications  
Tilt set for improved viewing

### Maintainability

Service profile identifier (SPID), up to 20 digits  
End-point service message  
Automatic TEI assignment  
Parameter downloading versions 1 and 2  
DMS 100 service profile management  
Auto SPID capability

### Accessories

Add-on button module (ABM for Model 9924 only)  
30 keys for call appearances, features,  
OneTouch numbers  
Wall mount kit  
Template printing program

### Power

AC or line powered: 24 to 60V DC  
3.0 Watts maximum; idle: 1.0 Watts  
(SRS-9924 with ABM: 4.0 Watts maximum; idle: 1.6 Watts)

### Standards

ANSI T1.605-1991  
(Power Source 2: 32 to 56.5V DC,  
8 Watts maximum; normal draw approximately 2.2 Watts)  
FCC Part 15, subpart J-Class B  
FCC Part 68  
UL 1950 3rd edition  
Telcordia compliance tested  
Switch vendor interoperability tested

### Environment

Operating  
• Temperature: 32° to 104°F (0° to 40°C)  
• Humidity: 20% to 80% (non-condensing)  
Storage  
• Temperature: -4° to 140°F (-20° to 60°C)  
• Humidity: 5% to 95% below 84°F (29°C)

### Physical Characteristics

(HxWxD)  
ISDN Set: 3.5 x 8.1 x 9.3” (89 x 205 x 235mm)  
4.8”H with tilt legs (121 mm)  
Weight: 2.42 lbs (1.1 kg)  
ABM: 3.2 x 2.7 x 9.3” (81 x 68 x 235mm)  
4.5”H with tilt legs (114 mm)  
Weight: 0.88 lbs (0.4 kg)

Features and Specifications subject to change without notice.

## Fujitsu Network Communications, Inc.

End User Products  
1000 St. Albans Drive, Raleigh, NC 27609  
Ordering Information 919.790.3449 FAX 888.329.4736  
Technical Support 800.228.ISDN (4736)  
www.fnc.fujitsu.com • www.fnc.fujitsu.com/products/view\_341.html

© Copyright 2001 Fujitsu Network Communications, Inc.  
SRS® is a registered trademark of Fujitsu Network Communications, Inc.  
FUJITSU (and design) is a registered trademark of Fujitsu Limited and is used with permission by its authorized licensees. All Rights Reserved.

SRS9912SRS9924/DS/3.0/06.01/CM